

Link do produktu: <https://dronexpert.eu/dji-transmission-high-bright-monitor-combo-p-15436.html>



DJI Transmission High-Bright Monitor Combo

Cena brutto	11 499,00 zł
Cena netto	9 348,78 zł
Dostępność	Dostępna mała ilość Zapytaj o dostępność/Wysyłka/Odbiór osobisty
Kod producenta	CP.RN.00000209.01
Kod EAN	6941565928917
Producent	DJI

Opis produktu







In the Box



Video Transmitter
× 1



High-Bright Remote Monitor
× 1



Remote Monitor Hood
× 1



WB37 Battery Adapter (TX)
× 1



WB37 Intelligent Battery
× 2



WB37 Battery Charging Hub (USB-C)
× 1



NP-F Battery Adapter (TX)
× 1



NP-F Battery Adapter (RX)
× 1



USB-C to LEMO Power Cable
× 1



RS Gimbal Mounting Plate
× 1



USB-C Cable
× 1



SDI Cable
× 1



DC Power Cable
× 1



DC to P-TAP Power Cable
× 1



Installation Toolkit
× 1



Protector Case
× 1



Ronin Video Transmission Antenna
× 2

Specifications

Weight	Video Transmitter Weight: Approx. 350 g / 0.77 lbs (excluding antennas) High-Bright Remote Monitor Weight: Approx. 727 g / 1.6 lbs (excluding antennas)
Dimensions	Video Transmitter: 127×87×26 mm (L×W×H, excluding antennas) High-Bright Remote Monitor: 213×135×51 mm (L×W×H, excluding antennas)
Operating Frequency	Non DFS Frequency Band: 2.4000-2.4835 GHz 5.150-5.250 GHz 5.725-5.850 GHz DFS Frequency Band: 5.250-5.350 GHz 5.470-5.600 GHz 5.650-5.725 GHz"
Transmitter Power (EIRP)	2.4000-2.4835 GHz: <33 dBm (FCC) <20 dBm (SRRC/CE/MIC) 5.150-5.250 GHz: <23 dBm (FCC/SRRC/MIC) 5.250-5.350 GHz: <30 dBm (FCC) <23 dBm (SRRC/MIC) 5.470-5.600 GHz, 5.650-5.725 GHz: <30 dBm (FCC) <23 dBm (CE/MIC) 5.725-5.850 GHz: <33 dBm (FCC/SRRC) <14 dBm (CE)

Max Bandwidth	40 MHz
Max Bitrate	40 Mbps
Power Consumption	11 W
Power Supply Voltage	6 to 18 V
Output Voltage	Power Output Port: 6 to 18 V
Operating Time	Video Transmitter: 3 hours 40 minutes ^[1] High-Bright Remote Monitor: 2 hours ^[1]
Input Video Format	3G SDI: YCbCr 4:2:2 10-bit HDMI RGB 4:4:4 1080p: 23.98/24/25/29.97/30/50/59.94/60fps 1080i: 50/59.94/60fps 720p: 50/59.94/60fps
Output Video Format	3G SDI: YCbCr 4:2:2 10-bit 1080p: 23.98/24/25/29.97/30/50/59.94/60fps 1080i: 50/59.94/60fps 720p: 50/59.94/60fps
Input Audio Format	SDI embedded, HDMI embedded
Output Audio Format	PCM
Video Transmission System	O3 Pro
Video Transmission Latency	68 ms ^[2] 100 ms ^[3]
Video Coding Format	H.264
Max Transmission Distance	6 km (FCC) ^[4] 4 km (CE/SRRC/MIC) ^[4]
Operating Temperature	-10° to 45° C (14° to 113° F)
Mirror Control Mode Supported Camera Models	ZV1/A7 III/A7S III/A7M III/A7R III/A7R IV/A7 IV/FX3/A7S II/A6600/A6400 and all Sony cameras that support BRAVIA (HDMI control).

Other

Notes	1. Measured at room temperature (25° C/77° F) with a fully charged WB37 battery. 2. Measured when shooting 1080p/60fps video. 3. Measured when shooting 1080p/24fps video. 4. In open environments free of obstructions or interference.
-------	---