

Link do produktu: <https://dronexpert.eu/dron-geprc-cinelog35-v2-hd-o3-gpsm10-fpv-drone-2650kv-p-15708.html>

Dron GEPRC CineLog35 V2 HD O3 GPS(M10) FPV Drone 2650KV



Cena brutto	3 099,00 zł
Cena netto	2 519,51 zł
Dostępność	Dostępna mała ilość Zapytaj o dostępność/Wysyłka/Odbiór osobisty
Producent	GEPRC

Opis produktu

Summary

Gathering the experience and evolution of the GEPRC team in all aspects, CineLog35 V2 is finally launched to the market with better performance.

CineLog35 v2 version integrated with O3 VTX. The CineLog35 V2 version of the main carbon plate and injection protection frame increased the 7075 aluminum column for structural strengthening.

The battery mounting method uses a tie with 7075 aluminum parts fixed. The power XT60E1-M plug is integrated with the carbon plate for convenient application. The protective frame for O3 Air Unit adds a memory card and USB port for easy data reading.

Equipped with F722-45A AIO and the new SPEEDX2 2105.5 motor, more power, with aggressive power system and faster response.

This is a 3.5-inch HD FPV cinematic FPV drone that integrates cinematic, freestyle, leisure, and safety to meet the user's requirements for flying and filming various scenes indoors and outdoors. The user's satisfied voice is the motivation for us to move forward.

Feature

1. New appearance design, strengthening carbon plate, hollow design, injection protection frame, noise reduction design, flight safety, silent.
2. Adopts the GEP F722-45A AIO V2 high performance flight controller.
3. Propeller Guard adds memory card and USB ports to O3 Air Unit for easy data reading
4. For O3 camera design independent under hanging shock absorption gimbal, to solve the camera IMU resonance issues, to achieve the optimal anti-shake effect.
5. SPEEDX2 2105.5 motor with HQ DT90 propeller, stable power output, and smooth flight feel.
6. Power cable using XT60E1-M plug and carbon plate integrated design, convenient application.
7. Battery installation method using a tie with 7075 aluminum parts fixed, solid and stable.
8. Carefully tuned 3.5-inch HD cinematic FPV with flexible and delicate flight feeling.

Specifications

- Model: Cinelog35 V2 HD O3
- Frame: GEP-CL35 V2
- Wheelbase: 142mm
- Gimbal plate: 2.0mm
- Top plate: 3.5mm
- Bottom plate: 1.5mm
- FC system: GEP-F722-45A AIO V2
- MCU: STM32F722RET6
- Gyro: ICM 42688-P

- OSD: Betaflight OSD w/AT7456E chip
- ESC: 8Bit 45A
- VTX: [O3 Air Unit](#)
- Camera: O3
- Antenna: 5.8G&2.4G
- Motor: SPEEDX2 2105.5-2650KV 6S
- Propeller: [HQProp D-T90MM](#)
- GPS: GEP-M10
- CineLog35 V2 HD O3 TBSNanoRX weight: 285.8g
- Receiver: PNP, GEPRC ELRS 2.4G, TBS Nano RX
- Recommended battery: LiPo 1050mah-1300mah
- Flight time: 5'00" -8' 30"

Includes

1 x Cinelog35 V2 HD O3

2 x HQProp D-T90MM 2 pairs

2x M20*250mm battery strap

2 x Battery Silicone Pads

1 x Set of screws

1 x L-shaped screwdriver (1.5mm)

1 x L-shaped screwdriver (2mm)

1 x L-shaped screwdriver (3mm)

1 x M5 wrench

1 x plastic tweezers

1 x Antenna fixed tube (pair)

1 x Keychain

1 x GP Camera Mounting Base

1 x Naked GP Camera Mounting Base

1 x Antenna Mounting Base

Screw package includes:

2x cup head screws M2*18

2x round head screws with pad M2*5.5

1x round head screws M2*12

2x Rivet nut M2

4x round head screws M2*8

4x round head screws M2*7

4x round head screws M2*6

2x round head screws M2.5*6

2x hexagonal screw M1.6*8

1x Flange nuts M5

2x Press Rivet Nuts_Brass color M2*1.9-OD4.9

2x Iron nut M2

2x Iron nut M2

2x Camera gimbal shock absorbing rubber

Tips: GPS Rescue 4.4 | Betaflight <https://betaflight.com/docs/wiki/archive/GPS-Rescue-v4-4>

Comparison Of Specifications

Version				
	Cinelog35 V2 HD O3	Cinelog35 V2 HD Wasp	Cinelog35 V2 HD Avatar	Cinelog35 V2 Analog
Flight Control	GEP-F722-45A AIO			
VTX	O3 Air Unit	Link	Avatar V2 (32G)	RAD 1W
Camera	O3 Camera	Runcam Wasp	Avatar HD V2(With Gyro)	Caddx Ratel2
Antenna	5.8G&2.4G	GEPRC Peano 5.8G LHCP		GEPRC Peano 5.8G RHCP
GPS	GEP-M8U			
Receiver	PNP / GEPRC ELRS24 / TBS NanoRX			
Motor	2105.5 2650kv			
Propeller	HQProp D-T90MM			
Flight time	5Mins—8Mins30s			
Recommend Battery	LiPo 6S 1050mah-1300mah			
Wheelbase	142mm			
Weight (TBS-NanoRX)	285.8g	277.2g	276.7g	263.8g
Notes	The above models are divided into the version without GPS and the version with GPS please select the corresponding options when purchasing			

Produkt posiada dodatkowe opcje:

Odbiornik: PNP DJI RC