

Dane aktualne na dzień: 26-04-2024 08:49

Link do produktu: <https://dronexpert.eu/zenmuse-x5s-z-obiektywem-p-11986.html>

ZENMUSE X5S Z OBIEKTYWEM



Cena brutto	9 999,00 zł
Cena netto	8 129,27 zł
Dostępność	Aktualnie niedostępny
Czas wysyłki	24 godziny
Kod EAN	6958265139161
Producent	DJI

Opis produktu

GENERAL

Name	Zenmuse X5S
Dimensions	140×98×132 mm
Weight	461 g

CAMERA

Supported Lens	DJI MFT 15mm/1.7 ASPH (With Balancing Ring and Lens Hood) Panasonic Lumix 15mm/1.7 (With Balancing Ring and Lens Hood) Panasonic Lumix 14-42mm/3.5-5.6 HD Olympus M.Zuiko 12mm/2.0 (With Balancing Ring) Olympus M.Zuiko 17mm/1.8 (With Balancing Ring) Olympus M.Zuiko 25mm/1.8 Olympus M.Zuiko 45mm/1.8 Olympus M.Zuiko 9-18mm/4.0-5.6
Sensor	CMOS, 4/3"
FOV	Effective Pixels: 20.8MP
Photo Resolutions	72° (with DJI MFT 15mm/1.7 ASPH) 4:3, 5280×3956 16:9, 5280×2970
Video Resolutions	H.264 C4K: 4096×2160 23.976/24/25/29.97/47.95/50/59.94p @100Mbps 4K: 3840×2160 23.976/24/25/29.97/47.95/50/59.94p @100Mbps 4K: 3840×1572 23.976/24/25/29.97p @100Mbps 2.7K: 2720×1530 23.976/24/25/29.97p @80Mbps 47.95/50/59.94p @100Mbps FHD: 1920×1080 23.976/24/25/29.97p @60Mbps 47.95/50/59.94p @80Mbps 119.88p @100Mbps H.265 C4K: 4096×2160 23.976/24/25/29.97p @100Mbps 4K: 3840×2160 23.976/24/25/29.97p @100Mbps 4K: 3840×1572 23.976/24/25/29.97p @100Mbps 2.7K: 2720×1530 23.976/24/25/29.97p @65Mbps

Photo Formats
Video Formats
Operation Modes
Still Photography Modes

Exposure Mode
Exposure Compensation
Metering Mode

AE Lock
Electronic Shutter Speed
White Balance

ISO Range

Video Captions
Anti-Flicker
PAL/NTSC

47.95/50/59.94p @80Mbps
FHD: 1920×1080
23.976/24/25/29.97p @50Mbps
47.95/50/59.94p @65Mbps
119.88p @100Mbps

C-DNG RAW
5.2K: 5280×2972
23.976/24/25/29.97p, up to 4.2Gbps
4K: 4096×2160, 3840×2160
23.976/24/25/29.97p, up to 2.4Gbps
4K: 4096×2160, 3840×2160
50/59.94p, up to 4.0Gbps

Apple ProRes
5.2K: 5280×2160
23.976/24/25/29.97p, 422 HQ @1.3Gbps
4K: 3840×2160
23.976/24/25/29.97p, 422 HQ @900Mbps
4K: 3840×2160
23.976/24/25/29.97p, 4444 XQ @2.0Gbps
DNG□JPEG□DNG+JPEG
RAW□ProRes□MOV□MP4
Capture, Record, Playback
Micro SD: Single shot, Burst Shooting:
3/5/7/10/14 frames, Auto Exposure Bracketing, 3/5 bracketed
frames at 0.7EV bias, Timelapse
SSD: RAW Burst Shooting:
3/5/7/10/14/20/∞ frames
Auto, Manual, Shutter, Aperture
±3.0 (1/3 increments)
Center-weighted metering,
Spot metering (area option 12x8)
Supported
8-1/8000s
Auto, Sunny, Cloudy, Incandescent,
Neon Custom (2000K-10000K)
100 - 6400 (Video)
100 - 25600 (Stills)
Supported
Auto, 50Hz, 60Hz
Supported

W opakowaniu :